



Hilti (Canada) Corporation

MSDS No.: 259C
 Revision No.: 007
 Revision Date: 08-27-09
 Page: 1 of 2

MATERIAL SAFETY DATA SHEET

Product identifier: FS-ONE High Performance Intumescent Firestop Sealant
Product use: Impedes the passage of fire, smoke and water through fire-rated walls and floors for up to 4 hours.
Supplier: Hilti (Canada) Corporation, 2360 Meadowpine Blvd., Mississauga, Ontario L5N 6S2
Originator: Hilti, Inc., P. O. Box 21148, Tulsa, Oklahoma, USA 74121
Emergency number: Chem-Trec: 1 800 424 9300

INGREDIENTS INFORMATION

Ingredient	CAS Number	% (wt.)	LC ₅₀ , (rat)	LD ₅₀ (rat)	TLV	STEL
Polyacrylate dispersion	Mixture	30 - 40	N/Av	N/Av	N/E	N/E
Calcium carbonate	01317-65-3	15 - 20	N/Av	N/Av	10 mg/m ³	N/E
Zinc borate	138265-88-0	10 - 15	N/Av	N/Av	NE	N/E
Ammonium polyphosphate	68333-79-9	05 - 10	N/Av	N/Av	N/E	N/E
Talc	14807-96-6	05 - 10	N/Av	N/Av	2 mg/m ³	N/E
Expandable graphite	12777-87-6	01 - 05	N/Av	N/Av	2 mg/m ³	N/E
Ethylene glycol	00107-21-1	01 - 05	10,876 mg.kg	4,700 mg/kg	100 mg/m ³	N/E
Polybutene	09003-29-6	01 - 05	N/Av	N/Av	N/E	N/E
Ferric oxide	01309-37-1	01 - 05	N/Av	N/Av	5 mg/m ³	N/E
Glass filament	65997-17-3	01 - 05	N/Av	N/Av	5 mg/m ³ (T)	N/E
Water	07732-18-5	01 - 05	N/Av	N/Av	N/E	N/E
Silicon dioxide	14808-60-7	< 0.2	N/Av	N/Av	0.1 mg/m ³	N/E

PHYSICAL PROPERTIES

Appearance / Physical state:	Red paste.	Odour:	Odourless.
Specific gravity (at 20°C):	1.5	VOC Content:	75.0 g/L
Vapour pressure (at 20°C):	23 mbar	Vapour density:	Not applicable.
Evaporation rate:	Not determined.	Boiling point:	Not determined.
Freezing point:	Not determined.	pH:	Not determined.
Coefficient of H2O / oil distrib:	Not determined.	Solubility in water:	Soluble.

FIRE AND EXPLOSION DATA

Flash point / Method:	Nonflammable.	Flammable limits:	Not applicable.
Conditions of flammability:	Not applicable.	Auto-ignition temperature:	Not applicable.
Means of extinction:	As appropriate for surrounding fire (e.g. Water, CO ₂ , Dry Chemical, Foam).		
Special fire fighting procedures:	None known. A NIOSH-approved self-contained breathing apparatus (SCBA) should be worn when fighting fires involving chemicals.		
Hazardous combustion products:	Thermal decomposition products such as oxides of carbon and nitrogen can be produced under fire conditions. See below.		
Sensitivity to mechanical impact / static discharge:	Not susceptible to mechanical impact or to a static discharge.		

REACTIVITY DATA

Stability:	Stable.	Conditions of reactivity:	None known.
Incompatible materials:	Strong acids, peroxides and oxidizing agents.		
Hazardous decomposition products:	None known. Thermal decomposition can yield oxides of carbon and nitrogen.		

TOXICOLOGICAL PROPERTIES

Routes of exposure: Skin contact Skin absorption Eye contact Inhalation Ingestion

Acute effects of exposure: **Eyes:** Can cause irritation or watering but injury is unlikely. **Skin:** Prolonged or repeated contact can cause irritation. **Inhalation:** No effects expected. **Ingestion:** Not a likely route of exposure. Considered to have a low acute oral toxicity.

Chronic effects of exposure: IARC classifies silica dust as a Group 1 carcinogen based upon studies of workers in industries where there has been long-term and chronic exposure to silica dust. This product is a paste and does not pose a dust hazard; therefore, this classification is not relevant.

Synergistic materials: None known.

FIRST AID MEASURES

Eyes: Flush with plenty of water. Call a physician if symptoms occur.

Skin: Wash with soap and water. Seek medical attention if any effects persist.

Inhalation: No ill effects expected. Should discomfort occur, move to fresh air.

Ingestion: Do not induce vomiting unless directed by a Physician. Contact a physician immediately.

Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure

PREVENTATIVE MEASURES

Engineering controls: General (natural or mechanically induced fresh air movements).

Eye protection: Safety glasses with side shields are recommended.

Skin protection: Impermeable gloves recommended.

Respiratory protection: None normally required.

Other: No additional measures are normally required.

Handling procedures and equipment: For industrial use only. Keep out of reach of children. Keep container closed when not in use. Do not get into the eyes. Avoid prolonged or repeated contact with the skin. Practice good hygiene; i.e., wash after using and before eating or smoking.

Storage requirements: Store in a cool dry area. Keep from freezing. Store between 5° and 25° C.

Spill, leak or release: Immediately wipe away spilled material before it hardens. Place in a container for proper disposal in accordance with all applicable local, state, or federal requirements.

Waste disposal: Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, provincial, and federal safety, health and environmental regulations.

Special shipping instructions: Avoid temperature extremes. Keep from freezing.

REGULATORY INFORMATION

WHMIS classification: D2A, D2B

HMIS codes: Health 1, Flammability 0, Reactivity 0, PPE A

TDG shipping name: Not regulated.

PREPARATION INFORMATION / CONTACTS

Prepared by: Hilli, Inc., Tulsa, OK USA **Date of Preparation:** August 27, 2009 **Emergency phone number:** 1 800 424 9300

Customer Service: Hilli (Canada) Corporation, Mississauga, Ontario; 1 800 363 4458

Health / Safety contacts: Hilli, Inc., Tulsa, OK USA; 1 800 879 6000, Jerry Metcalf (x1003704)

Abbreviations used: N/E = None Established. N/A = Not Applicable. N/Av = Not Available. R = as "respirable fraction", IARC: International Agency for Research on Cancer. HMIS: Hazardous Materials Identification System

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.