

TREMSTOP ACRYLIC WHITE - 15 SSG CSTREMSTOP ACRYLIC WHITE - 15 SSG CSVersion 1.5
REVISION DATE: 01/21/2008

Print Date 05/12/2010

SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION**Product Information**

Trade name : TREMSTOP ACRYLIC WHITE - 15 SSG CSTREMSTOP ACRYLIC WHITE - 15 SSG CS

Product code : 901806 385

Supplier : Tremco Canada division
220 Wicksteed Avenue
Toronto, ON M4H 1G7

Telephone : (416) 421-3300

Emergency Phone: : (613) 996-6666

Product use : Sealant

Preparation Information

Prepared by: : Sewnauth Raghunandan

Date: : 01/21/2008

Telephone : (416) 421-3300

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

White. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.

Eyes : Slightly irritating.

Ingestion : May cause irritation to the mouth, throat and stomach.

Skin : Irritant effect may be delayed.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 : HAZARDOUS INGREDIENTS

Chemical Name	CAS-No.	Weight % Range
Amorphous silica	7631-86-9	1.0 - 5.0
Propylene glycol	57-55-6	1.0 - 5.0
Titanium dioxide	13463-67-7	0.5 - 1.5
Chlorothalonil	1897-45-6	0.1 - 1.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

TREMSTOP ACRYLIC WHITE - 15 SSG CSTREMSTOP ACRYLIC WHITE - 15 SSG CSVersion 1.5
REVISION DATE: 01/21/2008

Print Date 05/12/2010

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash with water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5: FIRE / EXPLOSION HAZARDS

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings.
- Hazardous combustion products : Smoke, fumes.
- Protective equipment for firefighters : Not applicable. Product is not expected to burn.
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection equipment

TREMSTOP ACRYLIC WHITE - 15 SSG CSTREMSTOP ACRYLIC WHITE - 15 SSG CS

Version 1.5

Print Date 05/12/2010

REVISION DATE: 01/21/2008

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Use safety glasses if eye contact is likely.
- Protective measures : Use professional judgment in the selection, care, and use. Other equipment not normally required.
- Engineering measures : General ventilation is sufficient. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Amorphous silica	7631-86-9	Ontario TWA:	3 mg/m ³	Respirable particles.
		Ontario TWA:	10 mg/m ³	Inhalable particulate.
		ACGIH TWA:	3 mg/m ³	Respirable particles.
		ACGIH TWA:	10 mg/m ³	Inhalable particles.
		Ontario TWA:	10 mg/m ³	
Titanium dioxide	13463-67-7	Ontario TWA:	10 mg/m ³	Total dust.
		ACGIH TWA:	10 mg/m ³	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Physical State : Paste
- Form : Non-sag gunnable paste
- Color : White
- Odor : Acrylate
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : < 32 °C, < 90 °F
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Miscible
- Evaporation Rate: : Not available.
- Specific Gravity : 1.0931
- % Volatile Weight : 35 %

SECTION 10 - REACTIVITY / STABILITY

- Substances to avoid : Oxidizing agents. Strong acids. Strong bases.

TREMSTOP ACRYLIC WHITE - 15 SSG CSTREMSTOP ACRYLIC WHITE - 15 SSG CSVersion 1.5
REVISION DATE: 01/21/2008

Print Date 05/12/2010

SECTION 11 - TOXICOLOGICAL INFORMATIONAmorphous silica, CAS-No.: 7631-86-9
Acute oral toxicity (LD-50 oral)

22,500 mg/kg (Rat) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse) 15,000 mg/kg (Mouse)

Propylene glycol, CAS-No.: 57-55-6
Acute oral toxicity (LD-50 oral)

30,000 mg/kg (Rat) 18,000 mg/kg (Rabbit) 19,000 mg/kg (Dog) 23,900 - 31,800 mg/kg (Mouse) 18,400 - 196,000 mg/kg (Guinea pig)

Chlorothalonil, CAS-No.: 1897-45-6

Acute oral toxicity (LD-50 oral)
Acute dermal toxicity (LD-50 dermal)10,000 mg/kg (Rat)
10,000 mg/kg (Albino rat)**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATATDG / DOT Shipping Description:
NOT REGULATED**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

Canadian Regulations:

WHMIS Classification : D2A

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Other Regulations:

Regulatory VOC (less water and exempt solvent) : 36 g/l

TREMSTOP ACRYLIC WHITE - 15 SSG CSTREMSTOP ACRYLIC WHITE - 15 SSG CS

Version 1.5

Print Date 05/12/2010

REVISION DATE: 01/21/2008

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Sewnauth Raghunandan

Legend

- | | |
|---|--|
| ACGIH - American Conference of Governmental Hygienists | OSHA - Occupational Safety and Health Administration |
| DOT - Department of Transportation | PEL - Permissible Exposure Limit |
| DSL - Domestic Substance List | RCRA - Resource Conservation and Recovery Act |
| EPA - Environmental Protection Agency | STEL - Short Term Exposure Limit |
| HMIS - Hazardous Materials Information System | TLV - Threshold Limit Value |
| IARC - International Agency for Research on Cancer | TSCA - Toxic Substances Control Act |
| MSHA - Mine Safety Health Administration | TWA - Time Weighted Average |
| NDSL - Non-Domestic Substance List | V - Volume |
| NIOSH - National Institute for Occupational Safety and Health | VOC - Volatile Organic Compound |
| NTP - National Toxicology Program | WHMIS - Workplace Hazardous Materials Information System |

