

Chronic effects of exposure:

Synergistic materials:

None known.

None known.

 MSDS No.:
 259C

 Revision No.:
 010

 Revision Date:
 02-19-15

 Page:
 1 of 2

MATERIAL SAFETY DATA SHEET

Product identifier: FS-ONE High Performance Intumescent Firestop Sealant

Product use: Impedes the passage of fire, smoke and water through fire-rated walls and floors .

Supplier: Hilti (Canada) Corporation, 2360 Meadowpine Blvd., Mississauga, Ontario L5N 6S2

Originator Hilti, Inc., P. O. Box 21148, Tulsa, Oklahoma, USA 74121

Emergency number: Chem-1	Γrec: 1 800 424 9300					
	INGRE	DIENTS INF	ORMATION			
Ingredient	CAS Number	% (wt.)	LC ₅₀ , (rat)	LD ₅₀ (rat)	TLV	STEL
Polyacrylate dispersion	Mixture	30 - 40	N/Av	N/Av	N/Av	N/Av
Calcium carbonate Zinc borate	01317-65-3 1332-07-6	15 - 20 10 - 15	N/Av N/Av	N/Av N/Av	10 mg/m ³ N/Av	N/Av N/Av
Falc	14807-96-6	05 - 10	N/Av	N/Av	2 mg/m ³	N/Av
Ethylene glycol	00107-21-1	01 - 05	10,876 mg.kg	4,700 mg/kg	100 mg/m ³	N/Av
Ferric oxide	01309-37-1	01 - 05	N/Av	N/Av	5 mg/m ³	N/Av
	PHY	SICAL PRO	PERTIES			
Appearance / Physical state:	Red paste.		Odour:		Odourless.	
Specific gravity (at 20°C):	1.5		VOC Content:		75.0 g/L	
Vapour pressure (at 20°C):	23 mbar		Vapour density:		Not applicable.	
Evaporation rate:	Not determined.		Boiling point:		Not determined.	
Freezing point:	Not determined.		pH:		Not determined.	
Coefficient of H20 / oil distrib:	Not determined.		Solubility in water:		Soluble.	
	FIRE A	AND EXPLO	SION DATA			
Flash point / Method:	Nonflammable.		Flammable limits:		Not applicable.	
Conditions of flammability:	Not applicable.		Auto-ignition temperature:		Not applicable.	
Means of extinction:	As appropriate for surrounding fire (e.g. Water, CO_2 , Dry Chemical, Foam).					
Special fire fighting procedures:	None known. A NIOSH-approved self-contained breathing apparatus (SCBA) should be wor when fighting fires involving chemicals.					
Hazardous combustion products:	Thermal decomposition products such as oxides of carbon and nitrogen can be produced unde fire conditions. See below.					
Sensitivity to mechanical impact / static discharge:	Not susceptible to m	echanical im	pact or to a static of	discharge.		
	F	REACTIVITY	DATA			
Stability:	Stable.		Conditions of re	eactivity:	None known.	
Incompatible materials:	Strong acids, peroxides and oxidizing agents.					
Hazardous decomposition products:	None known. Therr	nal decompo	osition can yield CC	and CO ² .		
	TOXICO	OLOGICAL I	PROPERTIES			
Routes of exposure:				t 🗆 Inhalation	☐ Ingestion	
Acute effects of exposure:	 Skin contact ☐ Skin absorption ☐ Eye contact ☐ Inhalation ☐ Ingestion Eyes: Can cause irritation or watering but injury is unlikely. Skin: Prolonged or repeated 					
Acute effects of exposure:	contact can cause in exposure. Consider	ritation. In l	nalation: No effect	s expected. Inc	gestion: Not a li	ikely route
	• • •					

FIRST AID MEASURES

Eyes: Flush with plenty of water. Contact a physician if symptoms occur.

Skin: Wash with soap and water. Seek medical attention if any effects persist.

Inhalation: No ill effects expected. Should discomfort occur, move to fresh air.

Ingestion: Do not induce vomiting unless directed by a Physician. Contact a physician immediately.

Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure

PREVENTATIVE MEASURES

Engineering controls: General (natural or mechanically induced fresh air movements).

Eve protection: Safety glasses with side shields are recommended.

Impermeable gloves recommended. **Skin protection:**

Respiratory protection: None normally required.

Other: No additional measures are normally required.

Handling procedures and

For industrial use only. Keep out of reach of children. Keep container closed when not in use. Do not get into the eyes. Avoid prolonged or repeated contact with the skin. Practice good hygiene; i.e., wash after using and before eating or smoking. equipment:

Storage requirements: Store in a cool dry area. Keep from freezing. Store between 5° and 25° C.

Spill, leak or release: Immediately wipe away spilled material before it hardens. Place in a container for proper

disposal in accordance with all applicable local, state, or federal requirements.

Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, provincial, and federal safety, health and environmental regulations. Waste disposal:

Special shipping instructions: Avoid temperature extremes. Keep from freezing.

REGULATORY INFORMATION

D2A. D2B WHMIS classification:

HMIS codes: Health 1, Flammability 0, Reactivity 0, PPE A

TDG shipping name: Not regulated.

PREPARATION INFORMATION / CONTACTS

Prepared by: 1 800 424 9300 Hilti, Inc., Tulsa, Date of Preparation: **Emergency phone**

> OK USA February 19, 2015 number:

Customer Service: Hilti (Canada) Corporation, Mississauga, Ontario; 1 800 363 4458

Health / Safety contacts: Hilti, Inc., Tulsa, OK USA; 1 800 879 6000, Jerry Metcalf (x71003704)

Abbreviations used: N/E = None Established. N/A = Not Applicable. N/Av = Not Available. R = as "respirable

fraction". IARC: International Agency for Research on Cancer. HMIS: Hazardous Materials

Identification System

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.