

**MATERIAL SAFETY DATA SHEET**

**Product Identifier:** CP 606 Flexible Firestop Sealant  
**Product use:** Fire resistant acrylic based sealant for use in fire rated joint applications  
**Supplier:** Hilti (Canada) Corporation, 2360 Meadowpine Blvd., Mississauga, Ontario L5N 6S2  
**Originator:** Hilti, Inc., P. O. Box 21148, Tulsa, Oklahoma, USA 74121  
**Emergency number:** Chem-Trec: 1 800 424 9300

**INGREDIENTS INFORMATION**

Ingredient	CAS Number	% (wt.)	LC <sub>50</sub> , (rat)	LD <sub>50</sub> (rat)	TLV	STEL
Calcium carbonate	01317-65-3	50 - 55	N/Av	N/Av	N/E	N/E
Water	07732-18-5	15 - 20	N/Av	N/Av	N/E	N/E
Isononyl phthalate	28553-12-0	10 - 15	N/Av	N/Av	N/E	N/E
Polybutene	09003-29-6	01 - 05	N/Av	N/Av	N/E	N/E
Ethylene glycol	00107-21-1	01 - 05	N/Av	5500 mg/kg (mouse)	N/E	C:10Q, mg/m <sup>3</sup> (A)
<b>Pigments:</b>						
• Titanium dioxide	13463-67-1 <sup>1</sup>	01-05	N/Av	N/Av	10 mg/m <sup>3</sup>	N/E
• Red iron oxide	1309-37-1 <sup>2</sup>	01-05	N/Av	N/Av	5 mg/m <sup>3</sup> (R)	N/E
• Black iron oxide	28553-12-0 <sup>3</sup>	01-05	N/Av	N/Av	N/E	N/E

<sup>1</sup>CP606 white    <sup>2</sup>CP606 red    <sup>1,3</sup>CP606 grey

**PHYSICAL PROPERTIES**

<b>Appearance / Physical state:</b>	White, red, or grey paste.	<b>Odour:</b>	Mild odour.
<b>Specific gravity (at 20°C):</b>	1.55	<b>VOC Content:</b>	71.0 g/L
<b>Vapour pressure (at 20°C):</b>	Not applicable.	<b>Vapour density:</b>	Not applicable.
<b>Evaporation rate:</b>	Not determined.	<b>Boiling point:</b>	Not determined.
<b>Freezing point:</b>	Not determined.	<b>pH:</b>	Not determined.
<b>Coefficient of H<sub>2</sub>O / oil distrib:</b>	Not determined.	<b>Solubility in water:</b>	Miscible.

**FIRE AND EXPLOSION DATA**

<b>Flash point / Method:</b>	Nonflammable.	<b>Flammable limits:</b>	Not applicable.
<b>Conditions of flammability:</b>	Not applicable.	<b>Auto-ignition temperature:</b>	Not applicable.
<b>Means of extinction:</b>	Not applicable. As appropriate for surrounding fire (e.g. Water, CO <sub>2</sub> , Dry Chemical, Foam).		
<b>Special fire fighting procedures:</b>	None known. A NIOSH-approved self-contained breathing apparatus (SCBA) should be worn when fighting fires involving chemicals.		
<b>Hazardous combustion products:</b>	Not determined.		
<b>Sensitivity to mechanical impact / static discharge:</b>	Not susceptible to mechanical impact or to a static discharge.		

**REACTIVITY DATA**

<b>Stability:</b>	Stable.	<b>Incompatible materials:</b>	Strong oxidizing agents.
<b>Conditions of reactivity:</b>	None known.		
<b>Hazardous decomposition products:</b>	Not determined.		

**TOXICOLOGICAL PROPERTIES**

**Routes of exposure:**     Skin contact     Skin absorption     Eye contact     Inhalation     Ingestion  
**Exposure limits:**    See "Ingredients" section above.

**Acute effects of exposure:** **Eyes** – Slightly alkaline material; can cause irritation but injury is unlikely. **Skin** - Can cause irritation with some individuals. **Inhalation** - No effects expected. **Ingestion** - Not a likely route of exposure. Effects of ingestion have not been determined.

**Chronic effects of exposure:** None known.

**Synergistic materials:** None known.

#### FIRST AID MEASURES

**Eyes:** Flush immediately with plenty of water. Call a physician if symptoms occur.

**Skin:** Wash with soap and water. Seek medical attention if any effects persist.

**Inhalation:** No ill effects expected. Should discomfort occur, move to fresh air.

**Ingestion:** Do not induce vomiting unless directed by a Physician. Contact a Physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure

#### PREVENTIVE MEASURES

**Engineering controls:** General (natural or mechanically induced fresh air movements).

**Eye protection:** Safety glasses with side shields recommended.

**Skin protection:** Impermeable gloves recommended.

**Respiratory protection:** None normally required.

**Other:** No additional measures are normally required.

**Handling procedures and equipment:** For industrial use only. Keep container sealed when not in use to prevent curing of the product. Avoid contact with the eyes and skin. Practice good hygiene; i.e. wash after using and before eating or smoking.

**Storage requirements:** Keep out of reach of children. Store in a cool dry area. Keep from freezing. Shelf life is one year from date of manufacture if stored between 40° and 77° F (-5 - 25° C).

**Spill, leak or release:** Immediately wipe away spilled material before it hardens. Place in a container for proper disposal in accordance with all applicable local, state, or federal requirements.

**Waste disposal:** Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, provincial, and federal safety, health and environmental regulations.

**Special shipping instructions:** Avoid temperature extremes. Keep from freezing.

#### REGULATORY INFORMATION

**WHMIS classification:** D2B

**HMIS codes:** Health 0, Flammability 0, Reactivity 0, PPE B (glasses, gloves)

**TDG shipping name:** Not regulated.

#### PREPARATION INFORMATION / CONTACTS

**Prepared by:** Hilti, Inc., Tulsa, OK USA      **Date of Preparation:** August 09, 2009      **Emergency phone number:** 1 800 424 9300

**Customer Service:** Hilti (Canada) Corporation, Mississauga, Ontario; 1 800 363 4458

**Health / Safety contacts:** Hilti, Inc., Tulsa, OK USA; 1 800 879 6000, Jerry Metcalf (x1003704)

**Abbreviations used:** N/E = None Established. N/Av = Not Available. HMIS: Hazardous Materials Identification System. TLV = ACGIH Threshold Limit Value. STEL=Short Term Exposure Limit. R= Respirable Dust. A=Aerosol

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.