

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 1/10
(30711146/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

WALLTITE CM01 CT RESIN BULK

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component; industrial chemicals
Suitable for use in industrial sector: Polymers industry; chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: resin
Synonyms: Urethane System Resin Component

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
STOT RE	2 (oral)	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 2/10
(30711146/SDS_GEN_CA/EN)

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs (Kidney) through prolonged or repeated exposure (oral).
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye/face protection.
P260	Do not breathe dust/gas/mist/vapours.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P303 + P362	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
13674-84-5	>= 15.0 - < 20.0%	tris(2-chloro-1-methylethyl)phosphate
31568-06-6	>= 15.0 - < 20.0%	Ethanol, 2-((2-aminoethyl)amino)-, polymer with methyloxirane
140-07-8	>= 1.0 - < 3.0%	Ethanol, 2,2',2'',2'''-(1,2-ethanediyldinitrilo)tetrakis-
111-46-6	>= 1.0 - < 3.0%	diethylene glycol
2212-32-0	>= 0.3 - < 1.0%	2-((2-(dimethylamino)ethyl)methylamino)ethanol
1739-84-0	>= 0.3 - < 1.0%	1,2-dimethylimidazole
Trade Secret	>= 0.0 - < 0.1%	Trisubstituted aryl methane salt 1

The masked component(s) has only environmental hazards; HMIRA claims are not required for masked components with only environmental hazards.

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 3/10
(30711146/SDS_GEN_CA/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Information on: tris(2-chloro-1-methylethyl)phosphate

Symptoms: Overexposure may cause: convulsions, depression, hypoxemia, tremors

Information on: diethylene glycol

Symptoms: Overexposure may cause: vomiting, coma, abdominal cramps, lethargy, nausea, diarrhea, headache

Information on: Ethanol, 2,2',2'',2'''-(1,2-ethanediyl)dinitrilo)tetrakis-

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

water spray, dry powder, carbon dioxide, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 4/10
(30711146/SDS_GEN_CA/EN)

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids. Segregate from oxidants.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Storage stability:

Storage temperature: 15 - 25 °C

Storage duration: 6 Months

Protect against moisture.

The stated storage temperature is noted for health and safety in the workplace. With regard to Quality, please refer to the product specific Technical Bulletin.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 5/10
(30711146/SDS_GEN_CA/EN)

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	amine-like	
Odour threshold:	No applicable information available.	
Colour:	Purple	
pH value:	≥ 7	
Freezing point:	No applicable information available.	
Boiling point:	$> 140\text{ }^{\circ}\text{C}$	
Sublimation point:	No applicable information available.	
Flash point:	$> 94\text{ }^{\circ}\text{C}$	(closed cup)
Flammability:	not flammable	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be $5 - 15\text{ }^{\circ}\text{C}$ below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	$> 250\text{ }^{\circ}\text{C}$	
Vapour pressure:	$< 0.1\text{ hPa}$ ($25\text{ }^{\circ}\text{C}$)	
Density:	approx. 1.19 g/cm^3 ($20\text{ }^{\circ}\text{C}$)	
Relative density:	No applicable information available.	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	slightly soluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08

Version: 1.0

Page: 6/10

(30711146/SDS_GEN_CA/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Temperature: < 0 degrees Celsius

Incompatible materials

acids, oxidizing agents, isocyanates

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Oral

Type of value: ATE

Value: 3,104 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

No applicable information available.

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 7/10
(30711146/SDS_GEN_CA/EN)

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Origin of data: expert judgement

Irritation / corrosion

Assessment of irritating effects: May cause severe damage to the eyes.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Medical conditions aggravated by overexposure

Individuals with allergic history or pre-existing dermatitis should use extra precautions when handling this product. The substance may cause sensitization of the skin in particularly sensitive individuals.

12. Ecological Information

Toxicity

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 8/10
(30711146/SDS_GEN_CA/EN)

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

Toxicity to fish

Information on: tris(2-chloro-1-methylethyl)phosphate

LC50 (96 h) 51 mg/l, *Pimephales promelas* (Fish test acute, static)

LC50 (96 h) 56 mg/l, *Brachydanio rerio* (Fish test acute, static)

Information on: Trisubstituted aryl methane salt 1

LC50 (48 h) 0.1 mg/l, *Oryzias latipes* (other)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

LC50 (96 h) 0.1 mg/l, *Oryzias latipes* (JIS K 0102-71)

Literature data. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic invertebrates

Information on: tris(2-chloro-1-methylethyl)phosphate

EC50 (48 h) 131 mg/l, *Daphnia magna* (Daphnia test acute, static)

The statement of the toxic effect relates to the analytically determined concentration.

Information on: Trisubstituted aryl methane salt 1

LC50 (72 h) 1.9 mg/l, other (other)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

EC50 (48 h) 0.05 mg/l, *Daphnia magna* (Directive 79/831/EEC, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants

Information on: Trisubstituted aryl methane salt 1

No data available.

No data available.

No data available.

Information on: tris(2-chloro-1-methylethyl)phosphate

EC50 (72 h) 82 mg/l (growth rate), *Pseudokirchneriella subcapitata* (OECD Guideline 201, static)

Nominal concentration.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

Information on: Trisubstituted aryl methane salt 1

:

No data available.

aerobic

activated sludge, industrial/EC20 (0.5 h): 4 mg/l

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08

Version: 1.0

Page: 9/10

(30711146/SDS_GEN_CA/EN)

*DIN 38412 Part 27 (draft) aerobic
bacterium/EC10 (0.5 h): 0.75 mg/l*

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
The product has not been tested. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Safety Data Sheet

WALLTITE CM01 CT RESIN BULK

Revision date : 2018/06/08
Version: 1.0

Page: 10/10
(30711146/SDS_GEN_CA/EN)

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released; restriction on use and qty. / listed

This product contains a substance subject to a Significant New Activity (SNAc) as disclosed in the Canada Gazette.

The Minister of the Environment must be notified as outlined in the SNAc prior to engaging in any new activity.

See SNAc Notice in Canada Gazette for further details.

CGIIVol148No2p184-18

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 1 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2018/06/08

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET