

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 1/11
(30575896/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

SKYTITE® S-5001-L DGRY

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component; industrial chemicals
Suitable for use in industrial sector: Polymers industry; chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Synonyms: Elastomeric Roof Coating

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Asp. Tox.	1	Aspiration hazard
Flam. Liq.	3	Flammable liquids
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 2/11
(30575896/SDS_GEN_CA/EN)

STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P243	Take action to prevent static discharges.
P202	Do not handle until all safety precautions have been read and understood.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash with plenty of water and soap thoroughly after handling.
P240	Ground and bond container and receiving equipment.
P242	Use only non-sparking tools.

Precautionary Statements (Response):

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 3/11
(30575896/SDS_GEN_CA/EN)

P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P331	Do NOT induce vomiting.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.
P370 + P378	In case of fire: Use... to extinguish.

Precautionary Statements (Storage):

P233	Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
37244-96-5	>= 35.0 - <= 45.0%	Nepheline syenite
64742-47-8	>= 20.0 - <= 30.0%	Distillates, petroleum
13463-67-7	>= 5.0 - <= 15.0%	Titanium dioxide
22984-54-9	>= 2.0 - <= 7.0%	2-Butanone, O,O',O''-(methylsilyldyne)trioxime
112945-52-5	>= 1.0 - <= 3.0%	Silica

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 4/11
(30575896/SDS_GEN_CA/EN)

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

water spray, dry powder, carbon dioxide, foam, Dry sand, dry lime

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 5/11
(30575896/SDS_GEN_CA/EN)

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids. Segregate from oxidants.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2), Stove-lacquer KNS L-35

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Storage stability:

Storage temperature: 16 - 27 °C

Protect against moisture.

The stated storage temperature is noted for health and safety in the workplace. With regard to Quality, please refer to the product specific Technical Bulletin.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Titanium dioxide	OSHA PEL	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ;
	ACGIH TLV	TWA value 10 mg/m3 ;
Distillates, petroleum	ACGIH TLV	TWA value 200 mg/m3 Non-aerosol (total hydrocarbon vapor); Application restricted to conditions in which there are negligible aerosol exposures. Skin Designation Non-aerosol (total hydrocarbon vapor); The substance can be absorbed through the skin.
	OSHA PEL	TWA value 0.8 mg/m3 ; The exposure limit is calculated from the equation, $80\text{mg/m}^3 / (\% \text{SiO}_2)$, using a value of 100% SiO ₂ . Lower percentages of SiO ₂ will yield higher exposure limits. TWA value 20 millions of particles per cubic foot of air ;

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 6/11
(30575896/SDS_GEN_CA/EN)

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	viscous, liquid	
Odour:	slight odour	
Odour threshold:	No applicable information available.	
Colour:	white to grey	
pH value:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling point:	No applicable information available.	
Sublimation point:	No applicable information available.	
Flash point:	38.9 °C	(ASTM D4206)
	The product does not burn self-sustainingly.	
Flammability:	Flammable liquid	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 250 °C	
Vapour pressure:	No data available.	
Density:	1.30 g/cm ³ (20 °C)	
Relative density:	1.31	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	partly soluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 7/11
(30575896/SDS_GEN_CA/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

acids, oxidizing agents, isocyanates

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: No known acute effects.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 8/11
(30575896/SDS_GEN_CA/EN)

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Aspiration Hazard

May also damage the lung at swallowing (aspiration hazard).

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated oral uptake of the substance did not cause substance-related effects. Repeated inhalative uptake of the substance did not cause substance-related effects. Repeated dermal uptake of the substance did not cause substance-related effects.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Medical conditions aggravated by overexposure

Individuals with allergic history or pre-existing dermatitis should use extra precautions when handling this product. The substance may cause sensitization of the skin in particularly sensitive individuals.

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 9/11
(30575896/SDS_GEN_CA/EN)

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

The product has not been tested.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Adsorbable organically-bound halogen (AOX):

No data available.

Other ecotoxicological advice:

The product has not been tested. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Do not discharge substance/product into sewer system. Incinerate or dispose of in a licensed facility.

Container disposal:

Do not reuse empty containers. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove.

14. Transport Information

Land transport

TDG

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 10/11
(30575896/SDS_GEN_CA/EN)

Hazard class: 3
Packing group: III
ID number: UN 1993
Hazard label: 3
Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains HYDROTREATED LIGHT DISTILLATES (PETROLEUM))

Sea transport

IMDG

Hazard class: 3
Packing group: III
ID number: UN 1993
Hazard label: 3
Marine pollutant: NO
Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains HYDROTREATED LIGHT DISTILLATES (PETROLEUM))

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1993
Hazard label: 3
Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains HYDROTREATED LIGHT DISTILLATES (PETROLEUM))

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 2 Fire: 2 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2018/08/28

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Safety Data Sheet

SKYTITE® S-5001-L DGRY

Revision date : 2018/08/28
Version: 5.0

Page: 11/11
(30575896/SDS_GEN_CA/EN)

SKYTITE® S-5001-L DGRY is a registered trademark of BASF Canada or BASF SE
END OF DATA SHEET